

**In the Claims:**

Claim 1 (canceled)

2. (previously presented) The scale in accordance with claim 5, wherein said first base body comprises a first set of spaces defined between said first set of magnetic elements and said second set of magnetic elements are inserted into each one of said first set of spaces.

3. (previously presented) The scale in accordance with claim 5, wherein said first and second base bodies each have an identical geometry and magnetization.

Claim 4 (canceled)

5. (currently amended) A scale, comprising:  
a first base body, when considered in isolation, having a structure comprising:  
a first set of non-magnetizable supports support; and  
a first set of magnetic elements that are arranged laterally next to one of  
said first set of non-magnetizable supports support, are magnetized in a single identical direction  
and are arranged in a measuring direction wherein said first set of magnetic elements are  
arranged within a first set of tracks, wherein each of said first set of tracks are bounded only by  
two parallel walls of adjacent ones of said first set of non-magnetizable supports, and wherein  
said first set of tracks, viewed vertically with respect to said measuring direction, are arranged  
spaced apart from each other by a space;

a second base body, when considered in isolation from the first base body, has a structure comprising:

a second non-magnetizable support; and

a second set of magnetic elements that are arranged laterally next to said second non-magnetizable support, are magnetized in said single identical direction and are arranged in said measuring direction;

wherein said first base body and said second base body are put together such that:

in said measuring direction alternating ones of said first and second sets of magnetic elements are arranged and said first and second sets of magnetic elements have different magnetic orientations with respect to each other, wherein ~~said first set of magnetic elements are arranged within a first set of tracks, wherein each of said first set of tracks are bounded only by two parallel walls of adjacent ones of said first non-magnetizable supports, and wherein said first set of tracks, viewed vertically with respect to said measuring direction, are arranged spaced apart from each other by a space, and wherein said~~ one of said first set of non-magnetizable supports ~~support~~ and said second non-magnetizable support are arranged in at least said space; and wherein said first set of tracks are concentric with one another and said one of said first set of magnetizable supports and said second non-magnetizable support ~~supports~~ are arranged in the form of concentric rings between two of said first set of tracks.

6. (original) The scale in accordance with claim 5, wherein said first and second sets of magnetic elements are magnetized along an axis of symmetry of said scale.

7. (previously presented) The scale in accordance with claim 5, wherein each of said first set of magnetic elements comprises a plastic-bonded hard magnetic material.

8. (original) The scale in accordance with claim 7, wherein said hard magnetic material is defined by the group consisting of neodymium-iron-boron, samarium-cobalt or a ceramic magnetic material.

9. (currently amended) The scale in accordance with claim 5, wherein said one of said first set of non-magnetizable supports ~~support~~ is made of polyamide.

10. (currently amended) The scale in accordance with claim 5, wherein said one of said first set of non-magnetizable supports ~~support~~ is made of a castable, non-magnetizable material, and said first set of magnetic elements comprise a castable magnetic material.

11. (currently amended) A method for producing a scale, comprising:  
providing a first base body, when considered in isolation, having a structure  
comprising:

a first set of non-magnetizable supports ~~support~~; and

a first set of magnetic elements that are arranged laterally next to one of  
said first set of non-magnetizable supports ~~support~~, are magnetized in a single identical direction  
and are arranged in a measuring direction, wherein said first set of magnetic elements are  
arranged within a first set of tracks and wherein each of said first set of tracks are bounded only

by two parallel walls of adjacent ones of said first set of non-magnetizable supports, and wherein said first set of tracks, viewed vertically with respect to said measuring direction, are arranged spaced apart from each other by a space;

providing a second base body, when considered in isolation from the first base body, has a structure comprising:

a second non-magnetizable support; and

a second set of magnetic elements that are arranged laterally next to said second non-magnetizable support, are magnetized in said single identical direction and are arranged in said measuring direction; and

combining said first base body with said second base body by sticking them together such that:

in said measuring direction alternating ones of said first and second sets of magnetic elements are arranged and said first and second sets of magnetic elements have different magnetic orientations with respect to each other ~~wherein said first set of magnetic elements are arranged within a first set of tracks, wherein each of said first set of tracks are bounded only by two parallel walls of adjacent ones of said first non-magnetizable supports, and wherein said first set of tracks, viewed vertically with respect to said measuring direction, are arranged spaced apart from each other by a space,~~ and wherein said one of said first set of non-magnetizable supports support and said second non-magnetizable support are arranged in at least said space; and wherein said first set of tracks are concentric with one another and said first and second non-magnetizable supports are arranged in the form of concentric rings between two of said first set of tracks.

12. (original) The method in accordance with claim 11, wherein said first base body is produced by a dual injection-molding process by injecting a first material constituting said first support onto a second material that constitutes said first set of magnetic elements.

13. (original) The method in accordance with claim 12, wherein said second base body is produced by a dual injection-molding process by injecting a third material constituting said second support onto a fourth material that constitutes said second set of magnetic elements.

14. (currently amended) A position measuring system comprising:  
a scale, comprising:  
a first base body, when considered in isolation, having a structure  
comprising:  
a first set of non-magnetizable supports support; and  
a first set of magnetic elements that are arranged laterally next to  
said first non-magnetizable support, are magnetized in a single identical direction and are  
arranged in a measuring direction, wherein said first set of magnetic elements are arranged  
within a first set of tracks, wherein each of said first set of tracks are bounded only by two  
parallel walls of adjacent ones of said first set of non-magnetizable supports, and wherein said  
first set of tracks, viewed vertically with respect to said measuring direction, are arranged spaced  
apart from each other by a space;  
a second base body, when considered in isolation from the first base body,  
has a structure comprising:

a second non-magnetizable support; and

a second set of magnetic elements that are arranged laterally next to said second non-magnetizable support, are magnetized in said single identical direction and are arranged in said measuring direction; and

wherein said first base body and said second base body are put together such that;

in said measuring direction alternating ones of said first and second sets of magnetic elements are arranged and said first and second sets of magnetic elements have different magnetic orientations with respect to each other; ~~wherein said first set of magnetic elements are arranged within a first set of tracks, wherein said first set of magnetic elements are arranged within a first set of tracks, wherein each of said first set of tracks are bounded only by two parallel walls of adjacent ones of said first non-magnetizable supports, and wherein said first set of tracks, viewed vertically with respect to said measuring direction, are arranged spaced apart from each other by a space, and wherein said one of said first set of non-magnetizable supports support~~ and said second non-magnetizable support are arranged in at least said space; and wherein said first set of tracks are concentric with one another and said first and second non-magnetizable supports are arranged in the form of concentric rings between two of said first set of tracks; and

a scanning element, which is sensitive to a magnetic field, for scanning said first and second sets of magnetic elements.

15. (original) The position measuring system in accordance with claim 14, further comprising:

a second scale;

a reduction gear that drives both said scale and said second scale in a manner in which they are geared down in relation to each other;

a driveshaft coupled to said reduction gear, wherein said position measuring system is a multi-turn angle encoder for measuring an absolute position of said driveshaft over several revolutions.

16. (currently amended) The scale in accordance with claim 5, wherein said first set of magnetic elements are attached to said one of said first set of non-magnetizable supports support.

17. (currently amended) The scale in accordance with claim 16, wherein said first set of magnetic elements are injection molded to said one of said first set of non-magnetizable supports support.

18. (previously presented) The scale in accordance with claim 16, wherein said second set of magnetic elements are attached to said second non-magnetizable support.

19. (previously presented) The scale in accordance with claim 17, wherein said second set of magnetic elements are attached to said second non-magnetizable support.

20. (previously presented) The scale in accordance with claim 19, wherein said second set of magnetic elements are injection molded on said second non-magnetizable support.

21. (currently amended) The method in accordance with claim 11, further comprising attaching said first set of magnetic elements to said one of said first set of non-magnetizable supports support.

22. (currently amended) The method in accordance with claim 21, wherein said attaching comprises injection molding said first set of magnetic elements to said one of said first set of non-magnetizable supports support.

23. (previously presented) The method in accordance with claim 21, further comprising attaching said second set of magnetic elements to said second non-magnetizable support.

24. (previously presented) The method in accordance with claim 23, wherein said attaching comprises injection molding said second set of magnetic elements to said second non-magnetizable support.

Claim 25 (canceled)



26. (currently amended) The position measuring system in accordance with claim 14, wherein said first set of magnetic elements are attached to said one of said first set of non-magnetizable supports ~~support~~.

27. (currently amended) The position measuring system in accordance with claim 26, wherein said first set of magnetic elements are injection molded to said one of said first set of non-magnetizable supports ~~support~~.

28. (previously presented) The position measuring system in accordance with claim 26, wherein said second set of magnetic elements are attached to said second non-magnetizable support.

29. (previously presented) The scale in accordance with claim 27, wherein said second set of magnetic elements are attached to said second non-magnetizable support.

30. (previously presented) The scale in accordance with claim 29, wherein said second set of magnetic elements are injection molded on said second non-magnetizable support.

31. (currently amended) A scale, comprising:

a first base body, when considered in isolation, having a structure comprising:

a first non-magnetizable support in the form of a first ring; and

a first set of magnetic elements that are arranged only laterally next to said

first non-magnetizable support, are magnetized in a single identical direction and are arranged in a measuring direction so as to define a second ring that is concentric with said first ring;

a second base body, when considered in isolation from the first base body, has a structure comprising:

a second non-magnetizable support in the form of a third ring; and

a second set of magnetic elements that are arranged only laterally next to said second non-magnetizable support, are magnetized in said single identical direction and are arranged in said measuring direction so as to define a fourth ring that is concentric with said first, second and third rings and offset with respect to said second ring; and

wherein said first and second sets of magnetic elements have different magnetic orientations with respect to each other.

Claim 32 (canceled)

33. (previously presented) The scale in accordance with claim 31, wherein said first and second sets of magnetic elements are magnetized along an axis of symmetry of said scale.

34. (currently amended) The scale in accordance with claim 31, wherein said first set of magnetic elements are arranged within a first set of tracks, wherein said first set of magnetic elements are arranged within a first set of tracks, wherein ~~each of said first set of tracks are bounded only by two parallel walls of adjacent ones of said first non-magnetizable supports, and wherein said first set of tracks, viewed vertically with respect to said measuring direction, are~~

arranged spaced apart from each other by a space, and wherein said first non-magnetizable support and said second non-magnetizable support are arranged in at least said space.

35. (currently amended) A method for producing a scale, comprising:
- providing a first base body, when considered in isolation, having a structure comprising:
- a first non-magnetizable support in the form of a first ring; and
  - a first set of magnetic elements that are arranged only laterally next to said first non-magnetizable support, are magnetized in a single identical direction and are arranged in a measuring direction so as to define a second ring that is concentric with said first ring;
- providing a second base body, when considered in isolation from the first base body, has a structure comprising:
- a second non-magnetizable support in the form of a third ring; and
  - a second set of magnetic elements that are arranged only laterally next to said second non-magnetizable support, are magnetized in said single identical direction and are arranged in said measuring direction so as to define a fourth ring that is concentric with said first, second and third rings and offset with respect to said second ring; and
- combining said first base body with said second base body by sticking them together, wherein said first and second sets of magnetic elements have different magnetic orientations with respect to each other.

36. (currently amended) A position measuring system comprising:

a scale, comprising:

a first base body, when considered in isolation, having a structure

comprising:

a first non-magnetizable support in the form of a first ring; and

a first set of magnetic elements that are arranged only laterally next to said first non-magnetizable support, are magnetized in a single identical direction and are arranged in a measuring direction so as to define a second ring that is concentric with said first ring;

a second base body, when considered in isolation from the first base body, has a structure comprising:

a second non-magnetizable support in the form of a third ring; and

a second set of magnetic elements that are arranged only laterally next to said second non-magnetizable support, are magnetized in said single identical direction and are arranged in said measuring direction so as to define a fourth ring that is concentric with said first, second and third rings and offset with respect to said second ring; and

wherein said first base body and said second base body are put together and said first and second sets of magnetic elements have different magnetic orientations with respect to each other; and

a scanning element, which is sensitive to a magnetic field, for scanning said first and second sets of magnetic elements.

37. (previously presented) The position measuring system in accordance with claim 36, further comprising:

a second scale;

a reduction gear that drives both said scale and said second scale in a manner in which they are geared down in relation to each other;

a driveshaft coupled to said reduction gear, wherein said position measuring system is a multi-turn angle encoder for measuring an absolute position of said driveshaft over several revolutions.

38. (previously presented) The position measuring system in accordance with claim 36, wherein said first set of magnetic elements are attached to said first non-magnetizable support.

39. (previously presented) The position measuring system in accordance with claim 38, wherein said first set of magnetic elements are injection molded to said first non-magnetizable support.

40. (previously presented) The position measuring system in accordance with claim 38, wherein said second set of magnetic elements are attached to said second non-magnetizable support.

41. (previously presented) The position measuring system in accordance with claim 39, wherein said second set of magnetic elements are attached to said second non-magnetizable support.

42. (previously presented) The position measuring system in accordance with claim 40, wherein said second set of magnetic elements are injection molded on said second non-magnetizable support.